BARTELL LOBAL



TECHNICAL SPECS	
Voltage	460V
AMPS	25A
Power Output	15hp (11kW)
Phase	3-Phase
Weight	950 lbs (431kg)
Cycles	60Hz
Head Speed	0 - 1010 rpm
Motor Speed	0 - 1765 rpm
Grinding Plate Speed	0 - 105 rpm
Grinding Width	32" (81cm)
Head Diameter	10.5" (27cm)
Water Tank	7 gal (27L)
Hose Size	3" (75mm)
Length	57" (145cm)
Width	33" (83cm)
Height	52" (132cm)

P32N **X-SERIES GRINDER**

THE PREDATOR SERIES **DELIVERS AGGRESSIVE GRINDING & PERFECT POLISHING IN ONE GREAT MACHINE**

The secret of the Predator's success is the planetary motion, which eliminates the swirl marks left by conventional grinding methods. These grinders are manufactured with the highest standards in the industry, making them extremely reliable, productive, balanced and easy to use for any operator.

FEATURES

- · 32" working width
- · 4-head planetary design
- Variable speed
- · Forward & reverse setting
- American made
- Belt driven
- High production rates
- · Swing weight & travel wheel available
- · Uses SlideMag quick-change diamond tooling
- Fully compatible with the iShine Floor System
- · Simple adjustment to level to the floor surface
- Dust-free when used with suitable dust extractor





P32NDX



BartellGlobal.com