

# DRILLS & STANDS

PRODUCT CATEGORY



GRINDERS & POLISHERS



SHOTBLASTERS



FLOOR REMOVAL



SCARIFIERS



SCREED



TROWELS



BARTELL

morrison

SPE

Innovatech

CONTEC


PRECISION



SAWS



TOOLING & CONSUMABLES



DIAMOND BLADES



SPREADERS



COMPACTION



GENERATORS



MIXERS



BARTELL  
BARTELL GLOBAL

BARTELLGLOBAL.COM

# FEATURES AND BENEFITS



DMC6D

## FEATURES

- Wet and dry drilling capability
- Magnesium alloy construction for minimal weight and maximum strength
- Soft start electric motor
- Current and thermal overload protection
- Load warning system and indicator light
- 3 speed oil bath gearbox
- Mechanical clutch
- Integrated water feed system
- Two-in-one spindle for both 1-1/4" UNC and 1/2" BSP
- Built-in anti-seize ring
- Anti-vibration side handle reduces operator stress
- GFCI
- Included wrench
- 5/8"-11 bit adapter



HCD2200

## FEATURES

- Adjustable length shoulder stock
- Locking trigger
- Slip clutch for operator safety
- 16' - 14 gauge SJT cord
- Water feed with shutoff
- 18mm thread w/ adapters
- 360 degree adjustable side handle



4094  
4096

## FEATURES

- Two speeds: 450 and 900 rpm
- 20 amp motor
- Clutch protection protects gears and motor
- Built-in water swivel

## DRILL STANDS



HCDDS

## FEATURES

- Magnesium column
- Replaceable steel rack
- Replaceable polymer guides
- Dual side raise/lower
- 60mm replaceable collar
- Dual doughnut holders
- Adjustable leveling screws
- used with HCD2200 or DMC6D drills



CDS12VC

## FEATURES

- Magnesium column
- Replaceable steel rack
- Replaceable bronze guides
- 14" capacity
- Vacuum pump
- Switch box
- Adjustable leveling screws
- Use as bolt or vacuum base

# COMPLETE LINE



DMC6D



4094



4096



HCD2200

## TECHNICAL SPECS

<b>Power Input</b>	110V-120V: 1700W (15A)	<b>Weight</b>	24lbs	24lbs	9lbs (4kg)
<b>Voltage</b>	110V-120V~ 50Hz-60Hz	<b>Voltage</b>	120v	120v	110V
<b>No Load min-1</b>	930 / 1520 / 4270	<b>No Load RPM</b>	450 - 900	450 - 900	0-2200rpm variable
<b>Hand-held Capacity</b>	3" (80mm)	<b>Amps</b>	20	20	13A
<b>Rig-Mounted Capacity</b>	6" (152mm)	<b>Spindle</b>	1 - 1/14" -7	1 - 1/14" -7	-
<b>Spindle Thread External</b>	1-1/4" UNC	<b>Max HP</b>	4.8	4.8	-
<b>Spindle Thread Internal</b>	1/2" BSP				
<b>Neck Diameter</b>	60mm				
<b>Protection Class</b>	Class I with PRCD				
<b>Dimensions</b>	437mm x 115mm x 289mm				
<b>Net Weight</b>	14lbs (6.4kg)				



HCDDS



CDVS12VC

## TECHNICAL SPECS

<b>Model</b>	HCDDS	<b>Max Bit Diameter</b>	14"
<b>Column Size</b>	2" x 2"	<b>Column Length</b>	42"
<b>Column Length</b>	24"	<b>Column Diameter</b>	3" x 3"
<b>Mounting Type</b>	Bolt Down Base	<b>Weight Without Motor</b>	112lbs
<b>Weight</b>	6lbs	<b>Motor Options</b>	Milwaukee 4094 or 4096
		<b>Motor Weight</b>	24lbs
		<b>Motor</b>	110c 20 amp
		<b>Vacuum Pump</b>	110v 4 amp