

# FLOOR PLANERS

PRODUCT CATEGORY



GRINDERS & POLISHERS



SHOTBLASTERS



FLOOR REMOVAL



SCARIFIERS



SCREED



TROWELS



BARTELL

morrison



Innovatech

NORTH AMERICA  
CONTEC


METAL WORKS  
PRECISION



SAWS



TOOLING & CONSUMABLES



DIAMOND BLADES



SPREADERS



COMPACTION



GENERATORS



MIXERS



BARTELLGLOBAL.COM



# FEATURES AND BENEFITS



CT200

## FEATURES

- Dust free operation with integrated dust port
- Finite height adjustment by hand-wheel and quick lift by lever
- Robust, precision construction
- Proven reliability and quality
- Comprehensive range of cutters
- Long life cutter drum assemblies
- Belt tensioner and standard "V" belt drive

## APPLICATIONS

Surface texturing; Scarifying; Planing; Grooving; Cleaning; De-scaling; Removal of road markings



CT250

## FEATURES

- Dust free operation
- Robust, precision construction with proven reliability
- Extensive range of cutters available
- Long life cutter drum assemblies
- Optional integrated drive

## APPLICATIONS

Surface Texturing; Scarifying; Planing; Grooving; Cleaning; De-scaling; Removal of road markings, coatings, and membranes.



CT320

## FEATURES

The CT 320 is equipped with a variable speed drive unit. This, along with the ergonomically damped handle bars ensure reduced operator fatigue. An extensive range of cutting tools make this an extremely versatile machine. The CT 320 is capable of cutting depths down to 25mm. If deeper depths are necessary, the CT 320 can be ordered in the low chassis version, enabling cutting depths of 40mm.

The CT 320 is capable of cutting depths down to 25mm. If deeper depths are necessary, the CT 320 can be ordered in the low chassis version, enabling cutting depths of 40mm.

## APPLICATIONS

Surface Texturing; Scarifying; Planing; Grooving; Cleaning; De-scaling; Removal of road markings, coatings, and membranes.

# COMPLETE LINE



CT 200

## TECHNICAL SPECS

Part Number	CTPCT200	CTPCT200P
Maximum Working Width	8 in	8 in
Motor	2.8 HP, 230 Volt, 60 HZ, 11.6 Amps	2.7 hp Gas
Dimensions (H x L x W)	38 in x 31 in x 14 in	38 in x 31 in x 14 in
Weight	115 lbs	115 lbs



CT 250

## TECHNICAL SPECS

Part Number	CTPCT250	CTPCT250P
Maximum Working Width	10 in	10 in
Motor	12 hp 230 V, 60 Hz, 3 Phase, 26 Amps	12 hp Gas
Dimensions (H x L x W)	39 x 41 x 17 in	39 x 41 x 17 in
Weight	298 lbs	298 lbs
Dia. of Diamond Blade	7.9 in.	7.9 in.



CT 320

## TECHNICAL SPECS

Part Number	CTPCT320	CTPCT320LC (LOW CHASSIS)
Maximum Working Width	12.6 in	12.6 in
Motor	23 hp 480 V, 60 Hz, 3 Phase, 25 Amps	23 hp 480 V, 60 Hz, 3 Phase, 25 Amps
Dimensions (H x L x W)	43 x 43 x 24 in	43 x 43 x 24 in
Weight	507 lbs	507 lbs
Dia. of Diamond Blade	11.8 in	11.8 in
Dia. of Cutters	3 in	3 in