



GRINDERS & POLISHERS



SHOTBLASTERS



FLOOR REMOVAL



SCARIFIERS



SCREED



TROWELS



BARTELL morrison



Innovatech

CONTEC NORTH AMERICA


PRECISION METAL WORKS



SAWS



TOOLING & CONSUMABLES



DIAMOND BLADES



SPREADERS



COMPACTION



GENERATORS



MIXERS

WALK BEHIND FLOOR SCRAPERS

PRODUCT CATEGORY



BARTELLGLOBAL.COM

FEATURES AND BENEFITS



MS 230

COMPACT FLOOR SCRAPER, GREAT FOR REMOVING MANY TYPES OF FLOORING

This compact, easy to operate multistripper offers the user a solution for commercial and domestic applications. All components are manufactured from the highest grade materials ensuring strength and reliability.

- Fully adjustable chasis to adjust blade angle
- Large diameter wheels for excellent mobility and stability
- Simple clamp arrangement for quick and easy blade change
- Optimum weight distribution to ensure high work rate
- Handle height adjustable for operator control
- 230mm (9") working width

Typical Applications

- The removal of sheet vinyl, linoleum, cork, bonded carpet
- Woodblock, tiles, de-bonded membranes, sports surfaces
- Failed latex
- Build up of excess materials in production areas
- Mortar/Plaster droppings from concrete floors in new build

HEAVY-DUTY, SELF-PROPELLED FLOOR SCRAPER

This heavy duty power driven machine has proved to be a popular choice, setting new industry standards for all strippers of this type. The MS 330 offers the user a totally effortless high performance stripping machine for the removal of materials in the toughest possible conditions.

- Power driven support wheels to provide excellent forward traction
- Handle height adjustable for operator comfort
- Manually operated positive drive clutch for forward drive/freewheel
- Extremely powerful robust construction
- Simple clamp arrangement for quick and easy blade change
- Available in a choice of electric or petrol
- Blade angle adjustable to suit application

Typical Applications

- The removal of sheet vinyl, linoleum, cork, bonded carpet
- Woodblock, tiles, de-bonded membranes, sports surfaces
- Failed latex
- Build up of excess materials in factory production areas

MS 330

COMPLETE LINE



MS 230

TECHNICAL SPECS

	MS230 110V	MS230 230V
Type	MS230 110V	MS230 230V
Part No.	MS 230-1	MS 230-2
Power Output	2hp (1.5kW)	2hp (1.5kW)
Voltage	110V	230V
Cycles	50/60Hz	50/60Hz
Length	685mm (27")	685mm (27")
Width	380mm (15")	380mm (15")
Height	787mm (31")	787mm (31")
Weight	45kg (99 lbs)	45kg (99 lbs)
Work Width	230mm (9")	230mm (9")
Engine RPM	1400 RPM	1400 RPM



MS 330

TECHNICAL SPECS

Type	Electric 1 Phase	Electric 1 Phase	Electric 3 Phase	Petrol / Gas
Part No.	MS 330-1	MS 330-2		MS 330-4
Power Output	3hp (2.2kW)	3hp (2.2kW)	3hp (2.2kW)	5.5hp (4.1kW)
Voltage	110V	230V	400 / 460V	-
Cycles	50/60Hz	50/60Hz	50/60Hz	-
Length	1100mm (43.3")	1100mm (43.3")	1100mm (43.3")	1100mm (43.3")
Width	480mm (18.9")	480mm (18.9")	480mm (18.9")	480mm (18.9")
Height	1000mm (39.4")	1000mm (39.4")	1000mm (39.4")	1000mm (39.4")
Weight	132kg (290 lbs)	132kg (290 lbs)	132kg (290 lbs)	126kg (277 lbs)
Work Width	330mm (13")	330mm (13")	330mm (13")	330mm (13")
Engine RPM	2800 RPM	2800 RPM	2800 RPM	2800 RPM