

DFG 250

GRINDER POLISHER

RAPID GRINDING WITH COMPLETE CONTROL FOR THE OPERATOR



TECHNICAL SPECS

Part No.	DFG 250-2	DFG 250-1	DFG 250-4
Type	Gas/Petrol	Electric	Electric Twin Speed
Voltage	-	230V/400V/460V	230V/400V/460V
Power Output	13hp (9.7kW)	7.4hp (5.5kW)	5.6hp/4.3hp (4.2kW/3.2kW)
Cycles	-	50Hz/60Hz	50Hz/60Hz
Head Speed	700rpm/ 1400rpm	1400rpm	700rpm/ 1400rpm
Motor Speed	1400rpm/ 2800rpm	2800rpm	1400rpm/ 2800rpm
Length	44.1" (1120mm)	44.1" (1120mm)	44.1" (1120mm)
Width	26.4" (670mm)	26.4" (670mm)	26.4" (670mm)
Height	41" (1040mm)	41" (1040mm)	41" (1040mm)
Weight	268lbs (122kg)	352lbs (160kg)	352lbs (160kg)
Ballast Weight	-	1 x 44lbs (20kg)	1 x 44lbs (20kg)

FEATURES

- Ballast weight that allows for perfect grinding in all situations
- Simple foot pedal to raise or lower machine during use
- Robust Construction
- Dust extraction port
- Dust-free when used with suitable dust control vacuum
- Large diameter wheels for excellent mobility and stability
- Removable weight to vary grinding pressure
- Simple adjustment to level to the floor surface
- Fully adjustable handle
- Accurate grinding of concrete surfaces
- Removal of old floor coatings and contaminants
- Latex and adhesive removal
- Grinding and polishing of resin-based and tiled terrazzo
- Meets requirements of rental and contracting companies
- Fits easily in truck for easy transportation
- Fully compatible with the iShine Floor System

