

DMC6D

WET/DRY CONVERTIBLE DRILL

A HEAVY-DUTY DRILL YOU CAN TRUST ON THE JOB SITE



TECHNICAL SPECS

Power Input	110V-120V: 1700W (15A)
Voltage	110V-120V~ 50Hz-60Hz
No Load min-1	930 / 1520 / 4270
Hand-held Capacity	3" (80mm)
Rig-Mounted Capacity	6" (152mm)
Spindle Thread External	1-1/4" UNC
Spindle Thread Internal	1/2" BSP
Neck Diameter	60mm
Soft Start & Overload Protection	Included
Mechanical Safety Clutch	Included
Protection Class	Class I with PRCD
Dimensions	437mm x 115mm x 289mm
Net Weight	14lbs (6.4kg)

FEATURES

- Wet and dry drilling capability
- Magnesium alloy construction for minimal weight and maximum strength
- Improved cooling and increased durability
- Soft start electric motor
- Current and thermal overload protection
- Load warning system and indicator light
- 3 speed oil bath gearbox
- Mechanical clutch
- Integrated water feed system
- Can be mounted to a rig for larger drilling jobs
- Two-in-one spindle for both 1-1/4" UNC and 1/2" BSP
- Built-in anti-seize ring
- Anti-vibration side handle reduces operator stress
- GFCI
- Included wrench
- 5/8"-11 bit adapter
- Tool case
- Water feed
- Vacuum port

