

SPE 9ES

SHOTBLASTER

ENTIRELY EFFECTIVE ON BOTH
CONCRETE AND STEEL



TECHNICAL SPECS

Part No.	SPE 9ES-1	SPE 9ES-2	SPE 9ES-3
Voltage	110V	230V	400V/460V
Phase	Single	Single	Three
Blast Motor Output	3hp (2.2kW)	3hp (2.2kW)	5.5hp (4.1kW)
Cycles	50/60Hz	50/60Hz	50/60Hz
Cleaning Width	9.1" (230mm)	9.1" (230mm)	9.1" (230mm)
Length	31.5" (800mm)	31.5" (800mm)	31.5" (800mm)
Width	13.4" (340mm)	13.4" (340mm)	13.4" (340mm)
Height	33.1" (840mm)	33.1" (840mm)	33.1" (840mm)
Weight	196lbs (89kg)	196lbs (89kg)	220lbs (100kg)

FEATURES

- Manganese steel construction
- Fully adjustable handle height
- Deadman's handle automatically starts/stops blastmotor and opens/closes shot valve
- Front and rear supports wheels fully adjustable in height
- Grill fitted into lower separator hopper unit assembly to eliminate foreign objects being allowed into the blastwheel and causing damage
- Optional magnetic/steel seal system available
- 400V/460V optional high-power blast motor available
- Removes old coatings
- Provides non-slip surfaces
- Laitance removal on new concrete floors
- Texturing power floated concrete

