



WHEN A SMALL SPREADER JUST WON'T CUT IT!

TECHNICAL SPECS

Length	Up to 75' (23m)
Hopper Capacity	4.5 ft ³ (127L)
Engine	Honda GX160
Power	5.5hp
Maximum Load	600 lbs (272kg)
Discharge Height	2" (5cm) to 18" (122cm)
Hopper Weight	385 lbs (175kg)
2.5' (70cm) Section Weight	18 lbs (8kg)
5' (1.5m) Section Weight	32 lbs (28kg)
10' (3m) Section Weight	61 lbs (28kg)
Wheel Assembly Weight	270 lbs (123kg)
Trap Rock Capable?	yes

FEATURES

- Available in 2.5', 5' and 10' (0.7m, 1.5m, 3m) sections
- Material flow is adjustable from 2 ounces to 3 pounds (0.05 to 1.4kg) per square foot
- Bridge section weighs only 7 lbs (3.2kg) per foot
- Hydraulically agitated hopper weighs 308 lbs (140 kg)
- Flow rate control is independent from hopper travel speed
- Hopper height is adjustable from 2" (5.0cm) to 18" (45.7cm) over slab
- Bolted construction makes on-site length changes and adjustments quick and easy using everyday tools
- Metered flow valve assures precise application of expensive toppings
- Capable of spanning slabs from 10' (3 m) to 75' (23 m)
- Can be adjusted for trap-rock



MS20



MS40