

HIGHLY PRODUCTIVE & USER-FRIENDLY 8" SCARIFIER

Perfect for general surface preparation and coating removal on small/medium size jobs.

- Rigid, compact design
- Quick-lift pulls cutters in/out of cut
- Dust free when operated with a suitable dust collector, attached via 2 inch (5cm) dust extraction port
- Large diameter wheels for mobility and stability
- Locking fine-adjust wheel at the handle precisely increases/decreases cutting depth
- Firm engine mounting plate
- Front wheels protected from debris

Applications include:

- cleaning and texturing of concrete and asphalt
- removal of paint, rust, grease, ice deposits, line markings, and laitance
- concrete reduction, scabbling, grooving
- cleaning concrete formwork
- removal of concrete and plaster droppings



BEF200N

CT250

BEF275

BEF320

CT320

TECHNICAL SPECS

	Electric	Gas
Power Source	Electric	Gas
Power Output	3hp / 2.2kW	5.5hp / 4kW
Voltage	230V Single-Phase	-
Cutter Drum Speed	1738 rpm	1833 rpm
Cutter Diameter	up to 1.75"	
Starter	Switch	Recoil
Travel Method	Manually Propelled	
Length	39" (99cm)	
Width	16" (43cm)	
Height	37" (94cm)	
Weight	137 lbs (62kg)	127 lbs (58kg)
Max Working Width	8" (20cm)	
Wall Clearance	2.5" (7cm)	2" (5cm)
Engine/Motor RPM	2870 rpm	3000 rpm