

PLANING AND SCARIFYING MADE EASY!

Bartell Global's line of scarifiers has been proven by contractors around the world for over 30 years.

- Rigid, compact design
- Dust free when operated with recommended vacuum
- 11 inch (275mm) working width
- 2 inch (5cm) dust extraction port
- Forward mounted cutter drum for perfect balance
- Adjustable handle
- Includes drum and six flail shafts, heavy duty T.C.T. cutters
- Large wheels for excellent mobility & stability
- Side plate access for easy drum removal
- Accurate depth control for precision surface texture and maximum cutter life



Applications include:

- Cleaning and texturing concrete and asphalt
- Removal of paint, rust, grease, ice deposits, line markings, and concrete laitance
- Concrete reduction and scabbling
- Removal of roof chippings
- Grooving applications
- Cleaning concrete formwork and shuttering
- Non-slip finishes
- Removal of concrete and plaster droppings



BEF200N

CT250

BEF275

BEF320

CT320

TECHNICAL SPECS

Power Source	Electric	Gas
Power Output	10hp / 7.5kW	11hp / 8.2kW
Voltage	230V 3-Phase	-
Cutter Drum Speed	1640 rpm	
Cutter Diameter	up to 2.25"	
Blade Diameter	-	
Starter	Switch	Recoil
Travel Method	Manually Propelled	
Length	48" (122cm)	
Width	20" (51cm)	
Height	35.4" (90cm)	
Weight	331 lbs (150kg)	319 lbs (145kg)
Max Working Width	10.75" (27cm)	
Wall Clearance	2.5" (7cm)	
Engine/Motor RPM	2800 rpm	3600 rpm