BR2750 REVERSIBLE PLATE COMPACTOR





TECHNICAL SPECS	
Engine	Honda
Spec	GX200
Power Output	5.5hp (4.1kW)
Compaction Force	6063 lbf / 27 kN / 2750 kgf
Max Travel Speed	65'/min (20m/min)
Length	45" (1143mm)
Width	17" (432mm)
Height	36" (914mm)
Weight	335 lbs (152kg)
Plate Size	17" x 28" (43 cm x 70 cm)
Base Material	Ductile Iron

OVER 6000 LBS OF RELIABLE COMPACTION

The BR2750 is compact, affordable, and versatile – perfect for any general compaction project.

- Fully hydraulic reversing mechanism with flexible maneuverability allows the machine for forward, backward, and spot-on compaction
- Cast aluminum throttle lever for a more professional, stronger, and durable for tamping
- Full roll cage and built in lifting bale for increased engine and guide hook protection
- Cast aluminum belt cover for increased clutch and engine longevity
- · Ductile iron bases for increased strength
- Wheels that attach and flip down for easy transportation (on some models)
- Optional extension plates and urethane mat options available (on some models)
- Full speed in both forwards and reverse
- Specialized for compacting sand, trench, and patching













3R1570

BR2750 BR3570

BR4600

BR5100