HEPA DUST COLLECTORS









HD₂

- two motors
- two HEPA filters
- 2 Individual switches

HD3

- · three motors
- · three HEPA filters
- 3 Individual switches
- 30A outlet receptacle (50A optional)
- Two-stage filtering system comprised of one main conical filter, plus (1, 2, or 3) HEPA filters
- Reverse-air jet-pulse filter cleaning system effectively removes dust build-up on the filters
- Easy to use inlet closure door eliminates the need to remove hoses when pulsing and cleaning filters
- Easily connects to hand-operated power tools to extract concrete dust while cutting and grinding
- Equipped with a continuous-bag disposal system for effective dust collecting and safe & easy disposal of concrete dust

TECHNICAL SPECS				
MODEL	HD1	HD2	HD3	
Volts	120	120	120	230
Amps	8	16	16	12
Inlet Diameter	2.5" (63mm)			
Power (hp)	1.6hp	3.2hp	3.2hp	4.8hp
Air Flow (cfm)	120	240	288	356
Water lift (inches)	100	100	74	90
Pre-filter (F8) >99.5% @1.0um	16 ft² (1.5m²)	34 ft² (3m²)	48 ft² (4.5m²)	
HEPA Filter (H13) >99.99% @0.3um	13 ft ²	26 ft ²	39 ft²	
Length	26" (65cm)		31" (78cm)	
Width	16.5" (42cm)	23" (58cm)	23" (59cm)	
Height	42" (107cm)	50" (126cm)	58" (146cm)	
Weight	77 lbs (35kg)	119 lbs (54kg)	149 lbs (68kg)	141 lbs (64kg)

PRE-SEPARATOR

Providing additional separation to the dust extraction process

TECHNICAL SPECSMODELPS3Dust Tank
Capacity13 gal (50 liters)Inlet2.75" (7cm) inlet with
2" (5cm) adapter

21" (53cm)

22" (56cm)

 Height
 53" (135cm)

 Weight
 77 lbs (35kg)

Length

Width

