BARTELL C D D A L

TECHNICAL SPECS

S151

20%



SPRAY LARGE OUTDOOR AREAS, EQUIPMENT, AND BUILDINGS

Easily handles any water-soluble solution such as sanitizers, detergents, form oils, pigmented bond breakers, and pest control liquids. The S201 can handle up to 40% solids in curing compounds.

FEATURES

- Sprays materials with a variable pressure between 40 and 120 psi while constantly agitating material
- Easily handles form oils, pigmented curing compounds, bond breakers, soaps and detergents, pest control liquids, and most liquid type material
- Handles white pigment curing compounds up to 40% solids (S201); S151 can handle up to 20% solids
- Designed to be used from a truck, dock, work platform, dolly or skid
- S201 has exclusive wear adjustment feature that increases pump life as much as 200%
- Powered by dependable Honda engine
- Comes with 25' (7.6m) of 3/8" (0.95cm) hose and adjustable spray nozzle that can be disassembled for easy cleaning
- Pistol grip and atomizing nozzle options available
- CART AND BARREL SOLD SEPARATELY

Ensure that all proper PPE is worn at all times in accordance with the solutions you are spraying. Follow all solution manufacture guidelines for proper safety attire, application techniques and required application processes and steps, as outlined by the manufacture of the solution you are applying. Please refer to the S151 owners manual for proper use and operation.

S201

40%

40 - 120psi

Honda GX120

25' (7.6m), 50' (15.2m), 75' (22.8m)

8gal/minute (30L/min)

OR .03-.05 gal/min (3.8 - 6.4 oz/min)

120lbs (55kg)



MODEL

Pressure

Engine

Hose Lengths

Flow Rate

Max Solids

Weight