

# SPE16ES 16 INCH SHOTBLASTER



**SPE16ES SHOTBLASTER**



**16DC DUST COLLECTOR**

TECHNICAL SPECS		
MODEL	SPE16ES	SPE16DC
Voltage	380-415V	230V / 460V
Phase	3-Phase	
Blast Motor Output	15hp (11kW) 20hp (15kW)	-
Working Width	16" (41cm)	-
Length	49" (125cm)	68" (173cm)
Width	20" (51cm)	41" (103cm)
Height	49" (125cm)	63" (160cm)
Weight	882 lbs (400kg)	882lbs (400kg)
CFMS	-	1300/1560 ft <sup>3</sup> /min

- Blast unit constructed of manganese steel
- Dust collector fitted with integral compressor and reverse air jet pulsation system to allow continuous working
- Blasting width can be reduced for line removal and weld inspection
- Self-propelled variable-speed drive allows complete control
- Grill fitted into hopper assembly to keep foreign objects from entering the blastwheel and causing damage
- Capable of using up to S550 abrasive
- Fully machined blastwheel support bearing assembly (eliminates bearing problems, automatically self-aligns blastwheel components)
- Blastwheel can be rotated in both directions (optional extra)
- Can be dismantled to pass through a 24" (600mm) access hole in storage tanks



**HORNET**



**ELEPHANT**



**SPE9ES**



**SPE12ES**



**MODUL300**



**MODUL350**



**SPE16ES**



**SPE20ES**