

TECHNICAL SPECS		
MODEL	SPE20ES	SPE20DC
Voltage	380-415V	230V / 460V
Phase	3-Phase	
Blast Motor Output	30hp (22.5kW)	-
Working Width	20.5" (52cm)	-
Length	59.5" (151cm)	68" (173cm)
Width	23.5" (60cm)	41" (103cm)
Height	57" (145cm)	63" (160cm)
Weight	1459 lbs (662kg)	882lbs (400kg)
CFMS	-	1300/1560 ft ³ /min

- Blast unit constructed of manganese steel
- Dust collector fitted with integral compressor and reverse air jet pulsation system to allow continuous working
- Blasting width can be reduced for line removal and weld inspection
- Self-propelled variable-speed drive allows complete control
- Grill fitted into hopper assembly to keep foreign objects from entering the blastwheel and causing damage
- Capable of using up to S550 abrasive
- Fully machined blastwheel support bearing assembly (eliminates bearing problems, automatically self-aligns blastwheel components)
- Blastwheel can be rotated in both directions (optional extra)
- Can be dismantled to pass through a 24" (600mm) access hole in storage tanks



SHOTBLASTER



ELEPHANT













SPE9ES SPE12ES

MODUL300 MODUL350

SPE16ES

SPE20ES