## SPE9ES 9 INCH SHOTBLASTER





| TECHNICAL SPECS    |                |                 |
|--------------------|----------------|-----------------|
| Voltage            | 220V           | 380-415V        |
| Phase              | Single Phase   |                 |
| Blast Motor Output | 3hp (2.2kW)    | 5.5hp (4.1kW)   |
| Working Width      | 9" (23cm)      |                 |
| Length             | 31.5" (80cm)   |                 |
| Width              | 13.5" (34cm)   |                 |
| Height             | 33" (84cm)     |                 |
| Weight             | 196 lbs (89kg) | 220 lbs (100kg) |

Forward and reverse travel makes it easier and faster to move around your work space.

Fully machined blast-wheel support bearing assembly eliminates bearing problems and automatically self-aligns blast wheel components.

- · Manganese steel construction
- · Fully adjustable handle height
- · Automatic safety switch on handle automatially starts/stops blastmotor and opens/closes shot valve when released
- Front and rear supports wheels fully adjustable in height
- · Grill fitted into hopper assembly to keep foreign objects from entering the blastwheel and causing damage
- · Optional magnetic/steel seal system available
- · 400V/460V optional high-power blast motor available
- · APPLICATIONS:
  - Remove old coatings
  - Create non-slip surfaces
  - Remove laitance on new concrete floors
  - Texturize power-floated concrete

















**HORNET ELEPHANT** SPE9ES

MODUL300

MODUL350

SPE20ES