

CONCRETE VIBRATORS



EASILY CONSOLIDATE AND REMOVE AIR POCKETS

Includes three models that range from the S2MVM134 for small jobs requiring a head of 1.75" diameter or less, to the S2MVM225, the most versatile motor on the market that can power up to a 2.5" head, and finally the S2MVM325 which is a true work horse for the most demanding applications.

- High strength cast aluminum housing
- Shock absorbing frame and carry handle
- Water tight strain relief power cords
- Motors, heads, and shafts are interchangeable with other brands
- Comfortable shoulder strap available
- Serviceable parts easily available
- 3 models to match any size pour



QUICK DISCONNECT



SHAFT



MOTORS

MODEL		S2MVM134	S2MVM225	S2MVM325
Motor		1.75hp	2.25hp	3.25hp
Amps		15	17	19
kW		1.2	1.7	2.4
Maximum Head Size	Steel	1.75"	2"	2.5"
	Rubber	-	1.875" 2.75" short	2.75"

SHAFTS

PART #	SHAFT	PART #	SHAFT	PART #	SHAFT
MVS2	2' (0.6 m)	MVS14	14' (4.3 m)	MVS6P	6' (1.8 m)
MVS5	5' (1.5 m)	MVS16	16' (4.9 m)	MVS9P	9' (2.7 m)
MVS7	7' (2.1 m)	MVS18	18' (5.5 m)	MVS11P	11' (3.5 m)
MVS10	10' (3 m)	MVS21	21' (6.4 m)	MVS20P	20' (6 m)
MVS12	12' (37 m)	MVS3P	3' (0.9 m)		

*P designates "pencil shaft"

BACKPACK VIBRATOR



- GXH50 gas powered Honda engine
- Heads available .75" – 2.5"
- Shaft lengths from 6' (1.8m) – 18' (5.5m)
- Made in USA
- Quick release vibrator shafts for easy changes
- Parts interchangeable with many competitive brands

MOTOR	
MODEL	S2MVB212
Weight	29 lbs
Engine	Honda GXH50
Power Rating	2.50hp
Maximum Head	2.5' (6cm)
Maximum Shaft	21' (6.4m)
Vibrator Freq.	12000 vpm

POWERED by **HONDA**

STEEL HEADS

Part Number	Head Diameter	Radius of action	Insertion Spacing	Amplitude, center to side	Centrifugal Force	Capacity yd ³ /hr (m ³ /hr)	AVAILABLE OPTIONS			
							Standard	Short	Coated	Soft-Tip
MVH75P	0.75"	4" (102 mm)	6" (153 mm)	.070" (1.78 mm)	112 lbs (498 kg)	4 (3.64)	✓			✓
MVH100	1"	5" (127 mm)	7.5" (190.5 mm)	.075" (1.90 mm)	183 lbs (820 kg)	6 (5.46)	✓	✓		✓
MVH125	1.25"	7" (178 mm)	10.5" (267 mm)	.080" (2.03 mm)	430 lbs (1913 kg)	8 (7.28)	✓			✓
MVH112	1.5"	14" (356 mm)	21" (534 mm)	.090" (2.29 mm)	760 lbs (3380 kg)	12 (10.92)	✓	✓	✓	✓
MVH134	1.75"	18" (457 mm)	27" (685.5 mm)	.110" (2.79 mm)	1100 lbs (4893 kg)	24 (21.84)	✓			✓
MVH200	2"	22" (559 mm)	33" (838.5 mm)	.130" (3.30 mm)	1450 lbs (6450 kg)	35 (31.85)	✓	✓	✓	✓
MVH212	2.5"	28" (700 mm)	42" (1050 mm)	.145" (3.62 mm)	1525 lbs (3362 kg)	37 (33.40)	✓		✓	✓